



SYSCOM 1000T

1000FT Full-Duplex Intercom System Support Wireless Tally




Features

- 1000ft Full-Duplex Wireless Communication
- Support Wireless Tally and Remote Mute
- 1 Base Station Supports up to 8 Rechargeable Beltpacks
- LCD Screen, Easy to Operate
- 4 External High Gain Antennas
- DC/AC Dual Power Supply System
- USB Upgrade
- LEMO Headset & 3.5mm Earphone

Highlights



Remote Mute Beltpack
from Base station



Upgraded Rechargeable Beltpack



Professional Gooseneck
Microphone



Audio in/out Volume Adjustable

Packing List



Base Station



Beltpack



Professional Moving-coil
Side-ear Headset



AC Power Cable




TYPE-C Cable



1.9G High-Gain Base Station Antenna



Gooseneck Microphone



User Manual



Beltpack Charger

	Base Station	Beltpack
Interface	4 Antenna Interfaces(SMA--K Female Connector) AC Type Power Socket AC Input 4--pin XLR Male Connector DC Input 3.5mm Headphone Port 8--pin LEMO female Connector Headphone Socket, 3--pin XLR Female Connector Gooseneck Microphone Input; 3--pin XLR Female Connector Audio In 3--pin XLR Male Connector Audio Out DB25 Female Connector Tally Input USB 2.0 Type A USB Type--C	2 Antenna interfaces (SMA--K Female Connector) 3.5mm Headphone Port 8--pin LEMO Female Headphone Socket 3.5mm Tally Output USB Type--C
Power Supply Voltage Range	10--20V DC Input; 110--240V AC Input	4000mAh Polymer Lithium Battery
Frequency Response	300Hz to 4KHz	
Signal to noise Ratio	>50dB	
Distortion	<2%	
Working Range	Under LOS, 1000ft working range from Base Station to Beltpack	
Frequency Band	1.9GHz/2.4GHz	
Modulation Mode	GFSK	
Transmit Power	Maximum 24dBm	
Receiver Sensitivity	≤ -93dBm	≤ -93dBm
Bandwidth	1.728MHz	1.728MHz
Power Consumption	<6W	<2W
Size	(L x W x H): 482.6X175X44.4mm	(L x W x H): 120X71X25 mm
Net Weight	2921g	302g
Temperature Range	0 -- 40° C (Operating condition); -20 -- 60° C (Storage Model)	0 -- 40° C (Operating condition); -20 -- 60° C (Storage Model)
Certification	FCC, CE	FCC, CE