

Solidcom C1 Pro - Hub8S

Next-Level Team Talk

The Solidcom C1 Pro hub is designed with a brand-new 0B10 interface, supporting a more stable wired headset attachment to the hub in more professional applications. The wired headset of the hub-based system also features ENC technology that significantly rejects unwanted background noise and annoying echo. With a hub, multiple-system cascaded connection for expanded team communication is easily achieved.



Dual-Mic
ENC



PTT Function



150Hz-7kHz
Wideband Audio



1,100ft (350m)
Reliable Range



Ultra-long
Duration



Increased Portability
& Durability



Ready Out
of Box



Backward
Compatibility



A & B Dual
Grouping



Three-System
Cascaded Connection



ANNOUNCE
Function



PARAMETERS

	Hub	Wired Headset
Interface	RJ45 interface Power interface (DC interface) 4-wire audio interface (RJ45 socket) USB interface 2-wire audio interface PGM audio interface USB-C interface 0B10 headset interface RF antenna interface	USB-C interface
Antenna	External	Built-in
Power Supply	DC power, NP-F battery, V-mount battery, G-mount battery	700mAh lithium polymer battery
Operation Time	/	About 10 hours
Charging Time	/	About 2.5 hours
Volume Adjustment	Adjustment knob	Adjustable in 7 gears
Power Consumption	<4.5W	<0.3W
Dimensions	(LxWxH): 259.9mmx180.5mmx65.5mm (10.2"x7.1"x2.6")	(LxWxH): 186.9mmx75.6mmx188.6mm (7.4"x3"x7.4")
Net Weight	About 1300g (45.9oz) with the antennas excluded	About 170g (6oz) with the battery included
Transmission Range	1,100ft (350m) LOS	
Frequency Band	1880-1900 MHz: Europe, South Africa, much of Asia, Hong Kong, Australia, and New Zealand (10 channels) 1880-1895 MHz: Taiwan (8 channels) 1893-1906 MHz: Japan (J-DECT) 1910-1920 MHz: Brazil (10 channels) 1910-1930 MHz: Much of Latin America excluding Brazil 1920-1930 MHz: USA and Canada 2406-2474 MHz: Indonesia (SRD)	
Wireless Technology	Adaptive Frequency Hopping	
Modulation Mode	GFSK	
Wireless Power	≤21dBm (125.9mW)	
Bandwidth	1.728MHz	
RX Sensitivity	<-90dBm	
Frequency Response	150Hz-7kHz	
Signal-to-Noise Ratio	>55dB	
Distortion	<1%	
Input SPL	>115dB SPL	

PACKING LIST

Note: The quantity of the items depends on the product configuration.

Item	Quantity	
① Hub	X1	
② Remote Headset (With Blue Nameplate)	X8	
③ 0B10 Wired Headset (With Red Nameplate)	X1	
④ 8-Slot Charging Case	X1	
⑤ Headset Battery	X16	
⑥ Microphone Cushion	X9	
⑦ 12V/2A DC Adapter	X2	
⑧ Over-ear Leather Cushion	X9	
⑨ On-ear Foam Cushion	X9	
⑩ USB-A to USB-C Cable	X1	
⑪ High-Gain Antenna	X4	
⑫ Storage Case	X1	
⑬ User Manual	X4	
⑭ Warranty Card	X1	