

Solidcom C1 Pro

Next-Level Team Talk

The Solidcom C1 Pro, Hollyland's first-of-its-kind full-duplex wireless intercom headset system featuring dual-mic Environmental Noise Cancellation (ENC) technology, is incredibly lightweight and easy to use. This new-generation headset system features a wideband audio range of 150Hz to 7kHz, and a reliable LOS communication range of up to 1,100ft (350m).





Dual-Mic ENC



PTT Function



150Hz-7kHz Wideband Audio



1,100ft (350m) Reliable Range



Ready Out of Box



Backward Compatibility



| Specifications

Transmission Range	1,100ft (350m) LOS
Frequency Band	1.9 GHz (DECT) (varies by country and region)
Modulation Mode	GFSK
TX Power	≤ 21dBm (125.9 mW)
RX Sensitivity	< -9 0dBm
Battery Capacity	700mAh (2.66Wh)
Operation Time	Remote headset: > 10 hours (when ENC is turned ON) Master headset: > 5 hours (when ENC is turned ON and the master headset is connected with 5 remote headsets) Master headset: > 4 hours (when ENC is turned ON and the master headset is connected with 7 remote headsets)
Charging Time	About 2.5 hours
Frequency Response	ENC OFF: 150Hz-7kHz (fluctuation range: ±6dB) ENC ON: 150Hz-7kHz (fluctuation range: ±10dB)
Signal-to-Noise Ratio	71±2dB@94dBSPL, 1kHz
Distortion	< 1%@94dBSPL, 150Hz-7kHz
Microphone Type	Electret
Input SPL	> 115dBSPL
Output SPL	94±3dBSPL (@94dBSPL, 1kHz)
ENC	20dB±2 with two microphones (relative to environmental noise in all directions)
Net Weight	Single-EarWireless Stereo Headset: About 170g (6oz) with batteries included Double-EarWireless Stereo Headset: About 250g (9oz) with batteries included
Temperature Range	0°C to 45°C (working condition) -10°C to 60°C (storage condition)

Note: The frequency band and TX power vary by country and region.